



OQ PRODUCT HANDLING GUIDE

Isobutyl Acetate CAS # 110-19-0

Isobutyl Acetate is a clear, flammable liquid with a pleasant fruity odor. It is soluble in alcohols, ether, and hydrocarbons. It is not soluble in water. Isobutyl Acetate is stable under recommended storage

conditions. Isobutyl Acetate is available from OXEA in the following packages:

- DOT 111A100W1 Tank Cars

- DOT MC 307 or DOT 407 Tank Trucks
- Ship Tank and Barge

Storage

Recommended Blanketing	Air ^{1,2} or Dry Nitrogen ^{1,2,3}
Recommended Temperature	Ambient
Recommended Pressure	Atmospheric
Bulk Quantities	Outside, detached tanks
Small Containers	Cool, dry, well ventilated area

Handling

- Thoroughly review Safety Data Sheet before handling product.
- Keep containers closed when not in use.
- Open containers slowly to allow any excess pressure to vent.
- Keep away from heat, sparks, flame, or other sources of ignition.

- Protect small containers from physical damage.
- Use proper electrical grounding and bonding procedures when loading, unloading, and transferring.¹
- Refer to the OQ Safety Data Sheet for more information on materials to avoid.

- Use spark-resistant tools.
- Electrical equipment and circuits in all storage and handling areas must conform to requirements of national electrical code (Articles 500 and 501) for hazardous location.

See the National Fire Protection Agency (NFPA) #30 "Flammable and Combustible Liquids Code" and consult with qualified fire protection specialists to determine specific storage tank design requirements. Refer to the OQ Safety Data Sheet for more specific health and environmental

information and refer to the OXEA Product Descriptions for additional physical properties and general product information. Safety Data Sheet and Product Descriptions for Isobutyl Acetate are available through your OQ sales representative.

1. Refer to NFPA #77 "Static Electricity" for proper electrical grounding procedures.
2. See the National Fire Protection Agency (NFPA) #30 "Flammable and Combustible Liquids Code" and consult with qualified fire protection specialists to determine specific storage tank design requirements.
3. Blanketing may be used to retain quality in long-term storage conditions.

This information is based on our present state of knowledge and shall be intended to provide general notes on our products and their field of application. It shall therefore not be construed as guaranteeing specific characteristics of the products described and/or their suitability for a particular application. Any existing industrial property rights shall be observed. The quality of our products is warranted under our General Conditions of Sale.

Page 1 of 2
10260 OQ PHG EN V1.docx



OQ PRODUCT HANDLING GUIDE

Isobutyl Acetate CAS # 110-19-0

Materials of Construction for Storage and Transportation

Item	Recommended	Acceptable
Tank	Carbon Steel (rust free)	Stainless Steel ¹ , Lined Carbon Steel ² , Aluminum
Piping	Carbon Steel	Stainless Steel ¹ , Aluminum
Valves	Carbon Steel	Stainless Steel ¹ , Aluminum
Pumps	Cast Iron, Carbon Steel	Stainless Steel ¹
Relief Valves	Carbon Steel	Stainless Steel ¹
Gaskets	Glass Filled PTFE ³	PTFE ³
Pump Seals	Mechanical Seal: carbon to silicon carbide faces	-
Valve Packing	PTFE ³	Braided PTFE ³
Pipe End Connections	Welded and flanged system	Threaded with PTFE ³ tape thread lubricant
Heat Exchanger	Product Side: Stainless Steel ¹	Product Side: Carbon Steel
Hoses	Stainless Steel ¹	Butyl, Aluminum
Tank Truck	Stainless Steel ¹	Aluminum
Tank Car	Carbon Steel	Aluminum
Barge	Zinc Silicate or Epoxy Lined Carbon Steel	Stainless Steel ¹
Ship Tank	Zinc Silicate or Epoxy Lined Carbon Steel	Stainless Steel ¹

1. Type 304 or 316 Stainless Steel.
2. Lining refers to a high baked phenolic
3. Polytetrafluoroethylene.

This information is based on our present state of knowledge and shall be intended to provide general notes on our products and their field of application. It shall therefore not be construed as guaranteeing specific characteristics of the products described and/or their suitability for a particular application. Any existing industrial property rights shall be observed. The quality of our products is warranted under our General Conditions of Sale.

Page 2 of 2
10260 OQ PHG EN V1.docx